

VT760MKII Omni Headset Combination

Highest flexibility for your best performance.

The Voice Technologies VT760MKII is designed to fit any head contour and to free performers to focus on their performance! Ideal for TV, 2-way radio applications, public speaking and broadcast studio operations.

The VT760MKII has an extended frequency response and an onmidirectional polar pattern for outstanding clarity and natural sound. The flexible gooseneck enables the user to position the microphone for optimum sound and gain before feedback.

It is very comfortable and unobtrusive. A one size fits all soft earpiece is connected to the integrated earphone VT600. The microphone capsule and boom are moisture protected by molded injection.

Application area: Broadcast studio operations - Presentations



Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland Phone: +41 44 432 32 30, Email: info@vt-switzerland.com

www.vt-switzerland.com

VT760MKII Omni Headset Combination

Specifications:

Microphone:

Generating Element: Electret Condenser Polar Pattern: Omni-Directional Frequency Range: Sensitivity (@ 1kHz): 100Hz- 18 kHz

-43dB ±3dB 1V/microbar (7.1mV/Pa)

32dB "A" weighted Noise Level:

Max. Input SPL: 125dB

Impedance: 2.8 to 6.8 kOhms, nominal 4.4 kOhms

Bias/+VDC: 1.5V to 9.0V (max.)

Dynamic Range: 93db

62dB @94dB SPL Signal Noise Ratio:

Color: beige

Cable: Length 1.5m Ø 2mm

Weight: 42g

Wiring Configuration (3-wire):

+VDC Red Ground Copper Blue (Transparent) NF

Earphone:

Element: Subminature Magnetic Receiver


Frequency Response: 200Hz-8kHz 500 kOhm Impedance: Sensitivity: 104+/-3dB Distortion: 5% max. Color: beige

Wiring Configuration (2-wire):

Speaker:

Red Green

Frequency range:



Standard Accessories





Strap

Ear/Beige

Optional accessories



WS400/700

Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland Phone: +41 44 432 32 30, Email: info@vt-switzerland.com